

Wall mounted unit

FTX-KV



Energy saving during standby mode



Online controller via app

Discreet wall mounted unit providing high efficiency and comfort

› Discreet, stylish front panel blends easily with the wall, and matches all interior décors

› Online controller: control your indoor from any location with an app, via your local network or internet

FTX-KV + RX-K




Indoor unit			FTX	20KV	25KV	35KV	50KV	60KV	71KV
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++					A
		Pdesign	kW	2.00	2.50	3.50	5.00	6.00	7.10
		SEER		6.66	6.55	6.44	6.59	6.76	5.25
	Heating (Average climate)	Annual energy consumption	kWh	105	134	190	266	311	473
		Energy label		A++			A+		A
		Pdesign	kW	2.20	2.40	2.80	4.60	4.80	6.20
Casing	Colour		White						
	Dimensions Unit		HeightxWidthxDepth	286x770x225			295x990x263		
Sound power level	Cooling	dBA	55		58	59	60	62	
	Heating	dBA	55		58	59	61		
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dBA	39/33/25/20	40/33/26/20	43/34/27/20	43/39/34/31	45/41/36/33	46/42/37/34
	Heating	High/Nom./Low/Silent operation	dBA	39/34/28/23	40/34/28/23	43/35/29/26	42/38/33/30	44/40/35/32	45/41/36/33
Control systems	Infrared remote control		ARC480A11						
	Wired remote control		BRC944B2 / BRC073A1			BRC944B2 / BRC073			
Refrigerant	Type		R-410						
	GWP		2,087.5						

Efficiency data			FTX + RX	20KV + 20K	25KV + 25K	35KV + 35K	50KV + 50K	60KV + 60K	71KV + 71K
Cooling capacity	Nom.	kW	2.0	2.5	3.5	5.0	6.0	7.1	
Heating capacity	Nom.	kW	2.50	3.00	4.00	6.00	7.00	8.20	
Power input	Heating	Nom.	kW	0.52	0.69	1.00	1,579.00	1,928.00	2,570.00
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++					A
		Pdesign	kW	2.00	2.50	3.50	5.00	6.00	7.10
		SEER		6.66	6.55	6.44	6.59	6.76	5.25
	Heating (Average climate)	Annual energy consumption	kWh	105	134	190	266	311	473
		Energy label		A++			A+		A
		Pdesign	kW	2.20	2.40	2.80	4.60	4.80	6.20
Nominal efficiency	EER		3.98	3.78	3.43	3.58	3.65	2.61	
	COP		4.77	4.36	4.02	3.80	3.63	3.19	
Annual energy consumption		kWh	251	331	510	698	822	1,360	
Energy label		Cooling/Heating	-/-						

Outdoor unit			RX	20K	25K	35K	50K	60K	71K
Dimensions	Unit	HeightxWidthxDepth	mm	550x658x275			735x870x320		
Sound power level	Cooling	dBA	60		62	61	63	66	
	Heating	dBA	61		62	63	66		
Sound pressure level	Cooling	High	dBA	46	48	47	49	52	
	Heating	High	dBA	47	48	49	52		
Operation range	Cooling	Ambient	Min.-Max.	°CDB -10~-46					
	Heating	Ambient	Min.-Max.	°CWB -15~-18					
Refrigerant	Type/Charge/GWP		kg/TCO _{eq}	R-410A/0.74/1.5/2,087.5		R-410A/1.0/2.1/2,087.5	R-410A/1.13/2.4/2,087.5	R-410A/1.45/3.0/2,087.5	
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240					

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-025 03/16



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.